

# Product data sheet

JET 58 CYLINDRICAL BOLLARDS


JE-10582-T4-W40

LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	20 W	CRI	80
Total flux	1416 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	20 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	20 W	CRI	80
Total flux	1416 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	20 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 39.37 in

Diameter: 10.63 in

Weight: 7 kg

## Adjustability

Fixed

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 40 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Design

Color of housing: Black, White, Silver gray

## Protection

IP: 65

IK: 08

Surface temperature: 40°C