

Product data sheet

PURA SPOT R MAXI
911338.002.76
RZB




IP
20

IK
03


Series: Pura Spot R Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 65° vertically, spring fastening with no need for tools, heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools, passive cooling. LED included together with connected converter in separate gearbox. Available Colours: Traffic white, matt (RAL 9016) Type of Installation: Recessed ceiling mounting Dimensions: L 360, B 180, H 50, HE 170 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 2000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4400lm System power: 90W Beam Angle: 30° Number of fittings B10A: 4 Number of fittings B16A: 7 Number of fittings C10A: 9 Number of fittings C16A: 14 Inrush current: 14A Unified Glare Ratio: 18,0 EEC: B

Light output 1 (integrated)



Lamp type	LED	CCT	2000 K
Nominal lamp power	45 W	CRI	80
Total flux	2200 lm	LOR	100%
Luminous efficacy	49 lm/W	Total power	45 W

Light output 2 (integrated)



Lamp type	LED	CCT	2000 K
Nominal lamp power	45 W	CRI	80
Total flux	2200 lm	LOR	100%
Luminous efficacy	49 lm/W	Total power	45 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.09 in
Width: 14.17 in
Height: 6.06 in

Electric

System power: 90 W

Protection

IP: 20
IK: 03

Adjustability

Rotatable, Tilttable

Design

Color of housing: White