


# Product data sheet

BILLUND 1 STREET AND AREA LIGHTING LUMINAIRES  
BIU-90001-LC-T2-A-W40  
LIGMAN



- Lamp LED - CRI Ra > 70 - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency polycarbonate lens - Clear toughened glass - Surge protection 10kV

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	20 W	CRI	70
Total flux	2824 lm	LOR	100%
Luminous efficacy	141 lm/W	Total power	20 W

## Mounting mode

Pole integrated, Floor mounted

## Shape and measurements

Length: 17.05 in  
Width: 10.24 in  
Height: 3.90 in  
Weight: 4.5 kg

## Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 20 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Surface temperature: 40°C