


# Product data sheet

FLAT POLYMERO KREIS  
672387.002.1.07  
RZB




IP  
40

IK  
03

Item Number: 672387.002.1.07 Series: Flat Polymero Kreis Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Self-contained system, with integrated self-test and response via Dali bus, exclusively to the RZB 985405 monitoring system. Additional status indicator placed on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, , H 98mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: DALI-Sibe Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2600lm System power: 27W Beam Angle: 125° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 19,4 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	27.4 W	CRI	80
Total flux	2600 lm	LOR	100%
Luminous efficacy	95 lm/W	ULOR	16%
		Total power	27.4 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 3.86 in  
Diameter: 20.28 in

## Adjustability

Fixed

## Electric

System power: 27.4 W

## Protection

IP: 40  
IK: 03