


# Product data sheet

TALIA LED  
503003  
FLOS



• Bollard light for outdoor installation. • Configuration: extruded aluminium structure • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Clipped Uv-stabilized opal polycarbonate diffuser. The LED module is housed in a sealed transparent polycarbonate cylinder with compensation valve.

## Light output 1 (integrated)



Lamp type	LED	CCT	6000 K
Nominal lamp power	11 W	CRI	70
Total flux	123 lm	LOR	100%
Luminous efficacy	11 lm/W	ULOR	50%
		Total power	11 W

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 1.38 in

Width: 4.72 in

Height: 22.05 in

## Adjustability

Fixed

## Electric

System power: 11 W

Appliance Class: II

## Protection

IP: 65

IK: 08