
Product data sheet

LUCAS IV (WALL FITTING BEADED) 9.834.2072.16

LEIPZIGER LEUCHTEN






CRI



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure sodium vapour lamp | | |
|--------------------------------------|----------|-------|
| Nominal lamp power | 150 W | LOR |
| Lamp flux | 17000 lm | ULOF |
| Luminous efficacy | 80 lm/W | Total |
| CCT | 2000 K | Total |

ULOR Total flux 14091 lm Total power 176 W

83%

2%

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 176 W

25

Protection

IP: 55