



Product data sheet

SIRIUS 1200 - CC CEILING MOUNT
4232-H-2-688-XX
UNILAMP




Description A brand new linear light family features various mounting application types including In-ground walk over, wall mounted, wall recessed, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.

Light output 1




1 x LED			
Nominal lamp power	8.6 W	LOR	98%
Lamp flux	1049 lm	Total flux	1026 lm
Luminous efficacy	122 lm/W	Total power	8.6 W
CCT	4000 K		
CRI	85		

Light output 2




1 x LED			
Nominal lamp power	9 W	LOR	98%
Lamp flux	268 lm	Total flux	263 lm
Luminous efficacy	30 lm/W	Total power	9 W
CCT	0 K		
CRI	-50		

Light output 3



1 x LED			
Nominal lamp power	8.2 W	LOR	98%
Lamp flux	927 lm	Total flux	906 lm
Luminous efficacy	113 lm/W	Total power	8.2 W
CCT	8000 K		
CRI	-23		

Light output 4



1 x LED			
Nominal lamp power	6.8 W	LOR	98%
Lamp flux	380 lm	Total flux	371 lm
Luminous efficacy	56 lm/W	Total power	6.8 W
CCT	120 K		
CRI	-36		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.79 in

Width: 4.27 in

Height: 2.68 in

Adjustability

Fixed

Electric

System power: 32.6 W

Appliance Class: III

Protection

IP: 67

IK: 07