


Product data sheet

LADOR 1 FLOODLIGHTS,PROJECTORS
LD-50002-E-40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40 - Drive current 24 VDC - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request for LD-50021, LD-50031 - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	2.9 W	CRI	80
Total flux	90 lm	LOR	100%
Luminous efficacy	31 lm/W	Total power	2.9 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	2.9 W	CRI	-50
Total flux	15 lm	LOR	100%
Luminous efficacy	5 lm/W	Total power	2.9 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	2.9 W	CRI	-18
Total flux	90 lm	LOR	100%
Luminous efficacy	31 lm/W	Total power	2.9 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	2.5 W	CRI	-29
Total flux	61 lm	LOR	100%
Luminous efficacy	24 lm/W	Total power	2.5 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 2.44 in
Width: 2.44 in
Height: 4.13 in
Weight: 0.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 11.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: III

Protection

IP: 66
IK: 08
Surface temperature: 40°C