Product data sheet

LARGO WHITE 550LM 3000K RA>80 TRAILING EDGE DIMMING 7021986115697

SG ARMATUREN










Square wall luminaire with extra protection of diffuser. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 10W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



1 x LED	
Nominal lamp power	1
Lamp flux	550
Luminous efficacy	55 ln
CCT	300
CRI	

10 W	LOR	100%
550 lm	ULOR	11%
55 lm/W	Total flux	550 lm
3000 K	Total power	10 W
80		

Mounting mode

Wall mounted

Shape and measurements

Length: 9.45 in Width: 4.57 in Height: 9.45 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W Appliance Class: II

Protection

IP: 65 IK: 10