

Product data sheet

FLAT POLYMERO
311975.002.1.76
RZB




IP
40

IK
03

Series: FLAT POLYMERO Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 35 mm. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. TouchDim sensor capable. Light and/or presence sensors can be integrated. Colour: white Diameter: 460 mm Height: 120 mm Suspension length: 200-1300 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 19 W Rated luminous flux: 2150 lm Luminous efficiency: 113 lm/W Control gear: AC power, DALI dimmable Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2150 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	10%
		Total power	19 W

Mounting mode

Pendant

Electric

System power: 19 W

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Protection

IP: 40
IK: 03

Adjustability

Fixed