# Product data sheet

A.24 SOSP CURVA 90 R750 SHRP XF3000K BSV AQ73415


ARTEMIDE






A.24 SOSP CURVA 90 R750 SHRP XF3000K BSV

### Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	3.12 W

### Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	3.12 W

### Light output 3 (integrated)




LED	CCT	3000 K
3.12 W	CRI	90
216 lm	LOR	100%
69 lm/W	Total power	3.12 W
	3.12 W 216 lm	3.12 W CRI 216 lm LOR

# Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	3.12 W

# Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	3.12 W

# Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	3.12 W

# Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	3.12 W

# Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3.12 W	CRI	90
Total flux	216 lm	LOR	100%
Luminous efficacy	69 lm/W	Total pow	er 3.12 W

Mounting mode

Pendant

Shape and measurements

Length: 30.06 in Width: 30.06 in Height: 2.13 in

Adjustability

Fixed

Electric

System power: 25 W

Protection

IP: 20