


# Product data sheet

FLAT POLYMERO  
672059.002.7  
RZB




IP  
40

IK  
03

Item Number: 672059.002.7 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Mounting support body metal powder-coated, cover fixed by pressure lock, cover plastic (PMMA), opal, single battery system as standard with automatic self-test, status display on the luminaire. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, , H 120mm Lamp: LED + LED 1.5 W Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 3h Emergency Lighting System: automatic self-test Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) System power: 22W Beam Angle: 111° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 8,1 EEC: A++

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 19 W     | CRI         | 80     |
| Total flux         | 2100 lm  | LOR         | 100%   |
| Luminous efficacy  | 111 lm/W | ULOR        | 10%    |
|                    |          | Total power | 19 W   |

## Mounting mode

Wall mounted

## Shape and measurements

Height: 4.72 in  
Diameter: 18.11 in

## Adjustability

Fixed

## Electric

System power: 19 W

## Protection

IP: 40  
IK: 03