


Product data sheet

VICTORY 28W 4000K RA>80 CD
8246087083
SG ARMATUREN



Victory is an elegant, stylish and different post-top luminaire for modern urban environments. The unique organic design is at once both transparent and powerful. The oval asymmetrical light distribution provides an opportunity to use Victory in many applications where energy efficiency, product quality and aesthetic design are requested. Victory is equipped with the latest LED technology. New “state-of-the-art” design Harmonizes perfectly with modern urban environments An obvious choice for modern buildings, city areas, waterfronts Energy efficient – 104 lm/W No light pollution Contains no mercury Design Christian Hvidt Light distribution Direct. Light source LED 28W 3000K or 4000K Ra>80 SDCM:3 L80/B10>50,000 at Ta=25°C Control gear On/Off DYNADIM Philips Riegens Pr.2 Sweden Protection Class II, IP66, Ta=25°C, CE, IK09 Optic Direct symmetric Material and finish Housing/base: Die-cast aluminium, anodised, powder coated, textured grey. Holder and arm in stainless steel - Gear tray in special anticorrosive aluminium. Optic reflector in vacuum formed optic white PET - Front in tempered glass Mounting/Connection Posts: For mounting onto ø60mm or design pole (Poles to be ordered separately). The luminaire is pre-wired with 6.0m cable. The control gear and LED is mounted onto a gear tray. Wind projected area 800 cm2 - max 7 kg. Surge Protection Integrated Surge Protection (min. 4 kV). Extra surge protection for lightning strikes on request. Dimmable driver and other options on request. How to specify Post mounted designed IP66 rated LED luminaire. Base and top in die-cast aluminium, Optic in optic white PET. Base and top shade finished in textured sparkle grey. Arms and holder in stainless steel. Complete with control gear to operate LEDs, mounted onto a gear tray with plug/socket arrangement and pre-wired with power feed cable (6m). Post prepared for mounting onto 60mm or design pole. Protection Class II. As Riegens Victory range.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	2900 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	28 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 26.77 in
Width: 8.27 in
Height: 22.95 in

Adjustability

Fixed

Electric

System power: 28 W
Appliance Class: II

Protection

IP: 66
IK: 09