Product data sheet


MORITZ F VIII (1-ARMED) 9.213.1092.01 LEIPZIGER LEUCHTEN





Universal luminaire for mounting heights of 8.00 m to 16.00 m for different applications with high light requirements - Luminaire made of cast aluminium, varnished - Superior lighting due to asymmetrical and symmetrical, resp., luminous intensity distribution - Cover of single-pane safety glass, hinged - Cable protection braided hosing and closures made of stainless steel - All electrical parts fitted - Available in any required RAL or DB colour without extra price - Pole mounting, hot-dip galvanised and varnished, is part of the delivery - Please order separately: conical pole for ø 76 mm pole end Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium	1 x High pressure sodium vapour lamp					
Nominal lamp power	400 W	LOR	78%			
Lamp flux	49000 lm	Total flux	38179 lm			
Luminous efficacy	87 lm/W	Total power	440 W			
CCT	2000 K					
CRI	25					
1 x Metal halide lamp						
Nominal lamp power	400 W	LOR	78%			
Lamp flux	36000 lm	Total flux	28050 lm			
Luminous efficacy	64 lm/W	Total power	440 W			

THAY	"ATT
$\chi\chi A$	
\times	$+\times$
	+
XT	-tX
J	TL

Lamp flux	36000 lm	Total flux	
Luminous efficacy	64 lm/W	Total power	
CCT	4200 K		
CRI	85		

Mounting mode	Electric	
Pole top mounted	System power: 440 W	
Shape and measurements	Protection	
Length: 21.26 in Width: 21.26 in	IP: 55	

Created by luminaires.dialux.com (2 May, 2024)

Height: 6.89 in