


# Product data sheet

COMPASS  
03.3505/QR-CBC/50W/10°/24°/60°  
FLOS




Luminaire for halogen and high-pressure discharge lamps. Recessed body in black-painted metal. Die-cast aluminium alloy, powder-coated closing ring. Die-cast aluminium lamp support with heat dissipating element. Black thermoplastic anti-glare ring, 4 mm tempered glass cover. Stainless steel fixing brackets

## Light output 1




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W    | Socket      | Gu5.3   |
| Lamp flux          | 1012 lm | LOR         | 100%    |
| Luminous efficacy  | 20 lm/W | Total flux  | 1012 lm |
| CCT                | 3000 K  | Total power | 50 W    |
| CRI                | 100     |             |         |




### 1 x Halogen low voltage lamp without reflector

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 50 W    | Socket      | Gu5.3  |
| Lamp flux          | 995 lm  | LOR         | 100%   |
| Luminous efficacy  | 20 lm/W | Total flux  | 996 lm |
| CCT                | 3000 K  | Total power | 50 W   |
| CRI                | 100     |             |        |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W    | Socket      | Gx5.3   |
| Lamp flux          | 1182 lm | LOR         | 100%    |
| Luminous efficacy  | 24 lm/W | Total flux  | 1182 lm |
| CCT                | 3000 K  | Total power | 50 W    |
| CRI                | 99      |             |         |



1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W    | Socket      | Gu5.3   |
| Lamp flux          | 1025 lm | LOR         | 100%    |
| Luminous efficacy  | 20 lm/W | Total flux  | 1025 lm |
| CCT                | 3000 K  | Total power | 50 W    |
| CRI                | 100     |             |         |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.72 in

Diameter: 3.54 in

Adjustability

Fixed

Electric

System power: 50 W

Appliance Class: III

Protection

IP: 44