

# Product data sheet


KTRIBE T2 CRO/ALL.ARG.  
F6303004  
FLOS



IP  
20

Table luminaire providing diffused lighting. Base, rod support and diffuser support in die-cast, polished Zamak alloy. Polished aluminum tubular. Injection-molded, matte black PA (Nylon) base cover. Injection-molded PC (polycarbonate) opal inner diffuser. Transparent, blown glass outer diffuser with vacuum aluminum-coated finish inside. Injection-molded PC (polycarbonate) upper ring, completely transparent, aluminum-coated on the inner surface by vacuum aluminum coating. Electronic dimmer wired on cord for 0-100% light adjustment. FEP/PVC, UV-stabilized transparent power cord length 1500 mm.

## Light output 1



### 1 x Halogen low voltage lamp without reflector

Nominal lamp power	150 W	Socket	E27
Lamp flux	2500 lm	LOR	16%
Luminous efficacy	3 lm/W	ULOR	8%
CCT	2821 K	Total flux	408 lm
CRI	99	Total power	150 W

## Mounting mode

Table luminaire

## Shape and measurements

Length: 15.55 in  
Width: 15.55 in  
Height: 27.17 in

## Adjustability

Fixed

## Electric

System power: 150 W

## Protection

IP: 20