Product data sheet

ARENA 1200 WHITE MEDIUM 11830LM 4000K RA>80 ON/OFF 5703821174473

SG ARMATUREN










Arena is an energy efficient surface mounted IP23 luminaire for use in industry and storage. It is easy to install with hinged gear tray, and can be mounted either direct on ceiling (screws) or by using the mounting hooks for horizontal wiring. Arena is available in two lengths and with three different light distributions. Light distribution Direct (Medium) Light technic LED 79W 4000K Ra>80 SDCM 3 L90/B10 >70,000 hrs L80/B20 >100,000 hrs Control/Dimming On/off Protection Class I IP23 IK08 Energy and approvals CE Materials and finish Housing: Sheet steel Colour: White (RAL 9010, 20% gloss) Optics: PMMA Mounting/Connection Suspended or surface, Indoor Cable entry: end caps (knock out) 5 pole screwless terminal block Max. luminaires per circuit breaker: B10: 10, B16: 16, C10: 17, C16: 27

Light output 1



1 x LED
Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

79 W
11830 lm
150 lm/W
4000 K
80

LOR Total flux Total power 100% 11834 lm 79 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 50.00 in Width: 5.45 in Height: 2.35 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 79 W Appliance Class: I

Protection

IP: 23 IK: 08