


# Product data sheet

VARIOPLAST I  
672176.003.04  
RZB




IP  
00

IK  
08

Item Number: 672176.003.04 Series: Varioplast I Type of Protection: IP 55 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Mounting support body plastic (polycarbonate), cover plastic, opal (polycarbonate). Single battery system, automatic self-test with bus connection for feedback to the RZB Multidigit, RZB MWEBplus and S63 monitoring systems, can optionally be connected in non-maintained power mode (B) or maintained power mode (D). Lamps (LED) included in delivery. Available Colours: black Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 320, B 186, H 80mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Rated Operating Time: 8h Emergency Lighting System: MultiDigit Safety Marks: Ball impact proof in accordance with DIN 18032-03 Impact Protection: IK08 (5 Joule) Luminaire flux LED: 790lm System power: 8,4W Beam Angle: 120°/108° Unified Glare Ratio: 21,3 EEC: A++

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4000 K |
| Nominal lamp power | 8.4 W   | CRI         | 80     |
| Total flux         | 790 lm  | LOR         | 100%   |
| Luminous efficacy  | 94 lm/W | ULOR        | 6%     |
|                    |         | Total power | 8.4 W  |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 7.32 in  
Width: 12.60 in  
Height: 3.15 in

## Adjustability

Fixed

## Electric

System power: 8.4 W

## Protection

IP: 00  
IK: 08