Product data sheet

DOWNTOWN TRIM Ø215 03.0406/TC-TEL/26/32W


FLOS






Luminaires for embedded installation indoor with fluorescent lamps and of halogenuro metalist. Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.

Light output 1



1	Х	Compact	t fl	uorescent	l	amp

Nominal lamp power	32 W	Socket	Gx24Q-3
Lamp flux	2400 lm	LOR	49%
Luminous efficacy	37 lm/W	Total flux	1182 lm
CCT	4000 K	Total power	32 W
CRI	79		



1 x Compact fluorescent lamp)
------------------------------	---

Nominal lamp power	26 W	Socket	Gx24Q-3
Lamp flux	1800 lm	LOR	49%
Luminous efficacy	34 lm/W	Total flux	887 lm
CCT	2899 K	Total power	26 W
CRI	84		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.36 in Diameter: 8.46 in

Adjustability

Fixed

Electric

Protection

IP: 23

System power: 26-32 W