


Product data sheet

ARENA 1200 WHITE MEDIUM 11830LM 4000K RA>80 DALI
5703821174480
SG ARMATUREN



Arena is an energy efficient surface mounted IP23 luminaire for use in industry and storage. It is easy to install with hinged gear tray, and can be mounted either direct on ceiling (screws) or by using the mounting hooks for horizontal wiring. Arena is available in two lengths and with three different light distributions. Light distribution Direct (Medium) Light technic LED 77W 4000K Ra>80 SDCM 3 L90/B10 >70,000 hrs L80/B20 >70,000 hrs Control/Dimming DALI Protection Class I IP23 IK08 Energy and approvals CE Materials and finish Housing: Sheet steel Colour: White (RAL 9010, 20% gloss) Optics: PMMA Mounting/Connection Suspended or surface, Indoor Cable entry: end caps (knock out) 5 pole screwless terminal block Max. luminaires per circuit breaker: B10: 12, B16: 21, C10: 19, C16: 34

Light output 1



1 x LED			
Nominal lamp power	77 W	LOR	100%
Lamp flux	11830 lm	Total flux	11834 lm
Luminous efficacy	154 lm/W	Total power	77 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 50.00 in
Width: 5.45 in
Height: 2.35 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 77 W
Appliance Class: I

Protection

IP: 23
IK: 08