Product data sheet

LP NEST ALUMINIUM LED 3000K 34W CLO 91446-1001

LOUIS POULSEN








LP Nest Design: Bystrup Architechts Concept: The fixture emits an indirect, soft and symmetrical light. Reflections in the "lattice" create an attractive play of light within the fixture. Finish: Aluminium coloured with textured surface or graphite with textured surface, powder coated. Materials: Frame/Louvre: High pressure moulded aluminium. Top shade: Spun aluminium. Reflector: Anodised aluminium. Enclosure: Clear glass. Mounting: Pole dimension: Ø 115mm Installation cable: 5m, 5x1mm2 (Class I) or 5m, 4x1mm2 (Class II). Driver: Location in the post top. Class: Ingress protection IP66. Electric shock protection I w. ground, II w/o ground. IK09. Sizes and weights: Width x Height x Length (mm) 750 x 330 x 750 Max 12.1 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34 W	CRI	80
Total flux	2842 lm	LOR	100%
Luminous efficacy	84 lm/W	ULOR	4%
		Total power	34 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 12.99 in Diameter: 29.53 in

Adjustability

Fixed

Electric

System power: 34 W Appliance Class: II

Protection

IP: 66 IK: 09