


# Product data sheet

DOUBLE FUJI-FLAT WALL LIGHT  
7519-0-2-495-XX  
UNILAMP



Description FUJI is a family of shielded bollard. It gives symmetrical light distribution on illuminated surfaces. Fuji is operated with high power COB LED from world renowned manufacturer. It is generally installed in the walkways, parks, commercial areas and open spaces. It provides general lighting in the architectural environment where light pollution has to be controlled. We can supply the bollard at different heights according to customer designs. Anchor unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium reflector. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

## Light output 1



### 1 x Compact fluorescent lamp

Nominal lamp power	23 W	Socket	E27
Lamp flux	1500 lm	LOR	28%
Luminous efficacy	65 lm/W	ULOR	5%
CCT	3000 K	Total flux	417 lm
CRI	84	Total power	23 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 7.09 in

Width: 9.85 in

Height: 15.04 in

## Adjustability

Fixed

## Electric

System power: 23 W

Appliance Class: II

## Protection

IP: 65

IK: 08