


Product data sheet

POWERSVISION 56 RECESSED LOW BAY LUMINAIRES
PW69-GP054-T4-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 52.1 W | CRI | 80 |
| Total flux | 6681 lm | LOR | 100% |
| Luminous efficacy | 128 lm/W | Total power | 52.1 W |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 18.90 in
Width: 12.80 in
Height: 4.02 in
Weight: 9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 52.1 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 07
Surface temperature: 40°C