


Product data sheet

CYBERIA FX 371.LED 840 25500LM 210W IP65 RAL9005 DRV DIM DALI
5797265L3070
ES-SYSTEM



Oprawa nastropowa lub zwieszana OBUDOWA: aluminiowa, lakierowana, ramka w kolorze białym RAL 9016 DYPFUZOR: szkło hartowane lub laminowane, przezroczyste dostępne na zamówienie OPTYKA: wysokowydajne panele soczewkowe, 3 rozsyły światłości 60°, 90°, 30°x70° ZASILACZ: elektroniczny, na zewnątrz oprawy INNE: akcesoria zamawiane oddzielnie HOUSING: painted aluminum, white RAL 9016 frame DIFFUSER: transparent hardened or laminated glass, available upon request OPTICS: 3 light distribution variants: 60°, 90° and 30°x70° POWER SUPPLY: remote electronic power supply OTHER: accessories to be ordered separately GEHÄUSE: Aluminium, lackiert, RAL 9016 weißer Rahmen DIFFUSOR: Glas gehärtet oder laminiert, transparent, auf Anfrage erhältlich OPTIK: 3 Lichtverteilungsvarianten: 60°, 90° und 30°x70° STROMVERSORGUNG: elektronisch, außerhalb der Leuchte SONSTIGES: Zubehör separat zu bestellen

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	210 W	CRI	80
Total flux	25500 lm	LOR	100%
Luminous efficacy	121 lm/W	Total power	210 W

Mounting mode

Pendant

Shape and measurements

Length: 14.57 in
Width: 14.57 in
Height: 8.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 210 W
Voltage: 230 V AC
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 65
IK: 09