

Product data sheet


COMPASS BOX
03.1060/QR-111/100W/8°/24°/45°
FLOS



IP
20


Wall and ceiling luminaires 1,2 or 4 adjustable lights. Low voltage halogen, metal halide lamps or fluorescent lamps. Pressed steel, black painted optical body and extruded-aluminium outer structure with fixing system. Electrical connection and control devices incorporated in the luminaire.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1089 lm	LOR	100%
Luminous efficacy	22 lm/W	Total flux	1089 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	977 lm	LOR	101%
Luminous efficacy	20 lm/W	Total flux	983 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	G5.3
Lamp flux	1368 lm	LOR	100%
Luminous efficacy	14 lm/W	Total flux	1369 lm
CCT	3000 K	Total power	100 W
CRI	99		

Mounting mode

Ceiling mounted

Electric

System power: 50-100 W
Appliance Class: 0

Shape and measurements

Length: 6.50 in

Width: 6.50 in

Height: 5.31 in

Adjustability

Free

Protection

IP: 20