## Product data sheet

HOME 105 611984.0031 RZB





Series: Home 105 Type of Protection: IP 54 Protection Class: I Voltage: 200 - 240 V / 50 - 60 Hz Wall luminaire, direct beam. Housing: pressure die-cast aluminium, powder-coated. Driver included. LED included. Available Colours: anthracite metallic Type of Installation: Wall (surface) Dimensions: L 80, B 66, H 75 Lamp: LED Life time: 25000 h (L70/B50) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 110lm System power: 4W Beam Angle: 35°/19°/43°/43° Number of fittings B10A: 200 Number of fittings B16A: 320 Inrush current: 40A Unified Glare Ratio: 22,2 EEC: A+

## Light output 1 (integrated)



LED	CCT	3000 K
4 W	CRI	80
110 lm	LOR	100%
28 lm/W	ULOR	2%
	Total power	4 W
	4 W 110 lm	4 W CRI 110 lm LOR 28 lm/W ULOR

Mounting mode	Electric
Wall mounted	System power: 4 W
Shape and measurements	Protection
Length: 2.60 in	IP: 54
Width: 3.15 in	IK: 06
Height: 2.95 in	

## Adjustability

Fixed