## Product data sheet

EVA I 9.898.2036.00

LEIPZIGER LEUCHTEN






CCT

CRI



For medium light requirements, mounting height 3.00 - 5.00 m. - Impact-resistant opal polyethylene attachment - Large aluminium reflector for max. light output, underside in special white paint - Unit carrier made of die cast aluminium, corrosion-resistant, outside painted in color - All electrical components are arranged on a block - Adapter jack for connection - Available in any RAL or DB colour without surcharge - Please order pole dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



| 1 x High pressure sodium va | pour lamp |
|-----------------------------|-----------|
| Nominal lamp power          | 50 V      |
| Lamp flux                   | 3500 ln   |
| Luminous efficacy           | 46 lm/V   |


 wer
 50 W
 LOR
 82%

 3500 lm
 ULOR
 28%

 ry
 46 lm/W
 Total flux
 2858 lm

 2000 K
 Total power
 62 W

 25



## 1 x High pressure sodium vapour lamp

| Nominal lamp power | 70 W    | LOR         | 82%     |
|--------------------|---------|-------------|---------|
| Lamp flux          | 5600 lm | ULOR        | 28%     |
| Luminous efficacy  | 55 lm/W | Total flux  | 4573 lm |
| CCT                | 2000 K  | Total power | 83 W    |
| CRI                | 25      |             |         |

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 62-83 W

Protection

IP: 55