

Product data sheet

FLAT POLYMER0
311975.002.4
RZB




IP
40

IK
10

Series: FLAT POLYMER0 Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 35 mm. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. Colour: white Diameter: 460 mm Height: 120 mm Suspension length: 200-1300 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 19 W Rated luminous flux: 2000 lm Luminous efficiency: 105 lm/W Control gear: AC Strom, dim.Ph.an-/abschnitt Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	2000 lm	LOR	100%
Luminous efficacy	105 lm/W	ULOR	10%
		Total power	19 W

Mounting mode

Pendant

Electric

System power: 19 W

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Protection

IP: 40
IK: 10

Adjustability

Fixed