



Product data sheet

NOTUS 1 CROSS LOW UGR 4274MM
830
BRIGHT SPECIAL LIGHTING




Housing :Extruded aluminium Diffuser :Extruded PMMA | Cross Control Gear :Built-in electronic driver UGR :≤19 with special covers
Transmittance :80% IP :40 IK :04

Light output 1



1 x LED			
Nominal lamp power	116.7 W	LOR	100%
Lamp flux	17088 lm	Total flux	17088 lm
Luminous efficacy	146 lm/W	Total power	116.7 W
CCT	3114 K		
CRI	83		



1 x LED			
Nominal lamp power	84.9 W	LOR	100%
Lamp flux	11552 lm	Total flux	11552 lm
Luminous efficacy	136 lm/W	Total power	84.9 W
CCT	3114 K		
CRI	83		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 168.27 in
Width: 3.15 in
Height: 3.50 in

Adjustability

Free

Glare protection

Glare protection: UGR < 19

Electric

System power: 84.9-116.7 W
Ballast: ECG
Controller: Dimmable 0..10V, Dimmable 1..10V, DALI
Color adjustable
Appliance Class: I

Protection

IP: 40
IK: 04