

Product data sheet

PURA SPOT R MAXI
911306.003.1.76
RZB




IP
20

IK
03

Series: Pura Spot R Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Housing: powder coated die cast aluminium, rotates 356° horizontally and swivels 65° vertically, spring fastening with no need for tools, heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools, passive cooling. LED included together with connected converter in separate gearbox. Available Colours: deep black, matt (RAL 9005) Type of Installation: Recessed ceiling mounting Dimensions: D 180, H 50, HE 120 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2700lm System power: 27W Beam Angle: 15° Number of fittings B10A: 45 Number of fittings B16A: 80 Inrush current: 17A Unified Glare Ratio: 17,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	27 W	CRI	80
Total flux	2700 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	27 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.06 in
Diameter: 7.09 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Black

Electric

System power: 27 W

Protection

IP: 20
IK: 03