

Product data sheet

FLAT POLYMERO
311922.002.3
RZB




IP
40

IK
03

Series: FLAT POLYMERO Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 35 mm. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. Colour: white Diameter: 620 mm Height: 160 mm Suspension length: 350-1300 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 24 W Rated luminous flux: 2600 lm Luminous efficiency: 108 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	80
Total flux	2600 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	11%
		Total power	24 W

Mounting mode

Pendant

Electric

System power: 24 W

Shape and measurements

Height: 6.30 in
Diameter: 24.41 in

Protection

IP: 40
IK: 03

Adjustability

Fixed