

Product data sheet

FLAT POLYMERO KREIS SLIM
312085.002.3.191
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Slim Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Slave luminaire (SL), base: powder coated metal, cover fastening push lock, cover opal plastic (PMMA). Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 360, H 65 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2000lm System power: 21W Beam Angle: 122° Number of fittings B10A: 87 Number of fittings B16A: 139 Number of fittings C10A: 87 Number of fittings C16A: 139 Inrush current: 0,1A Unified Glare Ratio: 20,4 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	2000 lm	LOR	100%
Luminous efficacy	95 lm/W	ULOR	16%
		Total power	21 W

Mounting mode

Wall mounted

Shape and measurements

Height: 2.56 in
Diameter: 14.17 in

Adjustability

Fixed

Electric

System power: 21 W

Protection

IP: 40
IK: 03