



Product data sheet

RT 44
451170.002
RZB



Series: RT44 Type of Protection: IP 44 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz "Base: aluminium, powder-coated; end caps: plastic; diffuser:" plastic, opal, with push button. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 644, B 55, H 87 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 900lm System power: 10W Beam Angle: 180°/111° Unified Glare Ratio: 22,9 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 10 W | CRI | 80 |
| Total flux | 900 lm | LOR | 100% |
| Luminous efficacy | 90 lm/W | ULOR | 20% |
| | | Total power | 10 W |

Mounting mode

Wall mounted

Shape and measurements

Length: 2.17 in
Width: 25.35 in
Height: 3.43 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W

Protection

IP: 44
IK: 03