## Product data sheet

MINI MULTIPLE TRIMLESS FOR SMART KUP LED 4000K FLOOD GE BLACK 12535202+12556102


MODULAR






Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your chouce. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with Smart by adding the Smart frontrings to your recessed spot.

Light output 1





1 x LED			
Nominal lamp power	6.2 W	LOR	85%
Lamp flux	590 lm	Total flux	501 lm
Luminous efficacy	81 lm/W	Total power	6.2 W
CCT	4000 K		
CRI	90		
1 x LED			
Nominal lamp power	9.2 W	LOR	85%
Lamp flux	792 lm	Total flux	672 lm
Luminous efficacy	73 lm/W	Total power	9.2 W
CCT	4000 K		
CRI	90		

Mounting mode	Electric
Ceiling recessed, Wall recessed	System power: 6.2-9.2 W
Shape and measurements	Appliance Class: III
Length: 4.72 in	Protection
Width: 4.72 in	IP: 20
Height: 4.72 in	IK: 01
Weight: 0.69 kg	

## Adjustability

Free