

Product data sheet

LYCKSELE 1 LIGHT COLUMNS


LY-20001-N-W40

LIGMAN




- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing, extruded aluminium column and arm pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 140 km/h - Surge protection 10kV

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	36.8 W	CRI	80
Total flux	3431 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	36.8 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	36.8 W	CRI	80
Total flux	3431 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	36.8 W

Light output 3 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	36.8 W	CRI	80
Total flux	3431 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	36.8 W

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Height: 279.72 in

Diameter: 5.12 in

Weight: 68.3 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 110.4 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66

IK: 08

Surface temperature: 40°C