
Product data sheet

HOME 601 312181.002.76

RZB






L



Series: Home 601 Type of Protection: IP 40 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Frame: white powder-coated aluminium. Diffuser: plastic (PMMA), microprismatic/opal. Lateral LED light injection. LED included. External control gear (32mm high). Accessories for surface or pendant mount must be ordered separately. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 595, B 595, Lamp: LED Life time: 50000 h Colour Temperature: 3000K Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 3350lm System power: 35W Beam Angle: 87°/84° Inrush current: 20,4A Unified Glare Ratio: 17,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3350 lm	LOR	100%
Luminous efficacy	96 lm/W	Total power	35 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in Width: 23.43 in Height: 0.59 in

Adjustability

Fixed

Electric

System power: 35 W

Protection

IP: 40