



Product data sheet

SBR460[A60] IP54:HIT-CE 250W/E40
138-9650
WE-EF



IP54. Marine-grade aluminium alloy body. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Safety glass lens. Anodised aluminium reflector. 40°C ambient temperature rating for versions up to 250 W. Integral HPF control gear in thermally separated compartment. LPF versions are available on request. Optional (factory-installed) LIS lamp ignition sensor activates an integral tungsten halogen lamp following a cold start or a momentary power interruption. Deactivates the lamp once the main H.I.D. lamp reaches 50% of its objective brightness. 25°C ambient temperature rating. Suitable for the lighting of sports halls, indoor swimming pools and ice rinks, greenhouses, warehouses, factories, petrol stations, etc.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	250 W	Socket	E40
Lamp flux	26000 lm	LOR	73%
Luminous efficacy	69 lm/W	Total flux	19019 lm
CCT	3000 K	Total power	275 W
CRI	85		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 13.98 in
Width: 21.46 in
Height: 9.06 in

Electric

System power: 275 W

Protection

IP: 54