# Product data sheet

SPIKE WHITE W/ OUTLET 840LM 3000K RA>80 611911

SG ARMATUREN












Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct Light technic LED 11W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP44 IK08 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: Polycarbonat (PC) Mounting/Connection Surface, Outdoor Screwless terminal block

# Light output 1 (integrated)



Lamp type
Nominal lamp powe
Total flux
Luminous efficacy

LED	CCT
11 W	CRI
840 lm	LOR
76 lm/W	Total power

3000 K
80
100%
11 \//

# Mounting mode

Wall mounted

# Shape and measurements

Length: 6.53 in Width: 6.01 in Height: 6.69 in

#### Adjustability

Fixed

#### Design

Color of housing: White

#### Electric

System power: 11 W Appliance Class: I

### Protection

IP: 44 IK: 08