

Product data sheet

LESS IS MORE 50
312168.000.1
RZB




IP
20

IK
03

Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: extruded anodised aluminium profile. End caps made of plastic, light-deflecting segments made of plastic (ABS) aluminium vapour-plated, highly polished, symmetrical beam, with diffuser made of plastic (PC) opal. Anodised aluminium ceiling canopy. 2 point steel cable suspension infinitely height adjustable. Converter included. Lamp (LED) included. Available Colours: anodised aluminium Type of Installation: Pendant Dimensions: L 1140, B 53, H 65 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3800lm System power: 37W Beam Angle: 60°/58° Number of fittings B10A: 21 Number of fittings B16A: 34 Inrush current: 16A Unified Glare Ratio: 16,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	37 W	CRI	80
Total flux	3800 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	37 W

Mounting mode

Pendant

Electric

System power: 37 W

Shape and measurements

Length: 2.09 in
Width: 44.88 in
Height: 2.56 in

Protection

IP: 20
IK: 03

Adjustability

Fixed