

Product data sheet

VOLKMAR III (WALL FITTING)


9.840.0090.00

LEIPZIGER LEUCHTEN



For medium light requirements, mounting heights from 3.00 - 4.00 m. - Excellent uniform illumination, optimal glare protection - Mirror lamellae for light guidance and glare limitation made of premium highest grade aluminium, burnished and anodized - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



| | | | |
|------------------------------|---------|-------------|--------|
| 1 x Compact fluorescent lamp | | | |
| Nominal lamp power | 26 W | LOR | 55% |
| Lamp flux | 1800 lm | ULOR | 15% |
| Luminous efficacy | 35 lm/W | Total flux | 983 lm |
| CCT | 2899 K | Total power | 28 W |
| CRI | 90 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in

Diameter: 16.14 in

Electric

System power: 28 W

Protection

IP: 55