

# Product data sheet

INDIGO COMBO DELTA 600X600 830 VTB HL  
24190  
FAGERHULT



Installation Recessed mounting in suspended ceilings. Unventilated or ventilated ceilings. Two optional designs: VTB – for suspended ceilings with visible T-bars (15 or 24 mm). HB –for suspended ceilings with concealed T-bars and symmetrical ceiling tiles (thickness 20-22 mm). Four suspension fittings included. For fixed roofs (plaster etc.) suspension fittings for an HB body can be ordered separately. Connection Connected to 2.5 mm² 3-way terminal block 3 x 1.5 mm² (x2), with the possibility of through-wiring. 5 x 1.5 mm² (x2) when dimming. Can also be supplied with mains cable and earthed plug or chassis mounted snap-in connector. The luminaire housing and driver are connected via a Quick Connection System. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Delta – microprism louvre in acrylic (PMMA) with a thin opal diffuser (acrylic/PMMA) on the inside (PMMA). Dimming e-Sense Organic – PIR sensor with presence and daylight control. All luminaires have master/slave functionality with IR communications. Miscellaneous Enclosure class IP 40 under suspended ceilings and IP 20 above suspended ceilings. Class III applies to the luminaire body only. The supplied driver is Class II but should be connected to a functional Earth.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3714 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	35 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 23.46 in

Width: 23.46 in

Height: 4.96 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 35 W

Appliance Class: II

## Protection

IP: 40