


Product data sheet

FLAT POLYMERO KREIS SLIM
312084.002.1
RZB



IP
40

IK
03

Series: Flat Polymero Kreis Slim Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 65 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1200lm System power: 13W Beam Angle: 124° Number of fittings B10A: 136 Number of fittings B16A: 218 Number of fittings C10A: 136 Number of fittings C16A: 218 Inrush current: 0,15A Unified Glare Ratio: 19,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	17%
		Total power	13 W

Mounting mode

Wall mounted

Electric

System power: 13 W

Shape and measurements

Height: 2.56 in
Diameter: 11.81 in

Protection

IP: 40
IK: 03

Adjustability

Fixed