


Product data sheet

SPIKE WHITE TWILIGHT 840LM 3000K RA>80
611920
SG ARMATUREN



Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct Light technic LED 11W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class I IP44 IK08 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: Polycarbonat (PC) Mounting/Connection Surface, Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 11 W | CRI | 80 |
| Total flux | 840 lm | LOR | 100% |
| Luminous efficacy | 76 lm/W | Total power | 11 W |

Mounting mode

Wall mounted

Shape and measurements

Length: 6.53 in
Width: 6.01 in
Height: 6.69 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 11 W
Appliance Class: I

Protection

IP: 44
IK: 08