Product data sheet

MINI MULTIPLE TRIMLESS FOR SMART KUP LED 2700K FLOOD GE WHITE STRUC 12535009+12556109

MODULAR









Highly versatile Twenty years after its initial launch, Mini multiple is still a coveted luminaire. Mini multiple is the reference of our architectural lighting portfolio. The technology is on full display and allows this luminaire to fit well into both a minimalist and an industrial-chic environment. The gimbaled system allows you to direct the light source at any angle of your chouce. Mini multiple has a very subtle alu trim. Available in one-, two-, three- and four lamps versions in different colours. Connect Mini multiple with Smart by adding the Smart frontrings to your recessed spot.

Light output 1



6.2 W
519 lm
77 lm/W
2700 K
90

L	OR	92%
Т	otal flux	476 lm
Т	otal power	6.2 W



1 x LED			
Nominal lamp power	9.2 W	LOR	
Lamp flux	667 lm	Total flux	
Luminous efficacy	67 lm/W	Total power	
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Length: 4.72 in Width: 4.72 in Height: 4.72 in Weight: 0.69 kg

Adjustability

Free

Electric

System power: 6.2-9.2 W Appliance Class: III

Protection

IP: 20 IK: 01 92% 612 lm 9.2 W