

# Product data sheet


NORA I (W. SHIELD ON SIDE FACING BUILDING OPAL ATTACHMENT)  
9.771.1032.36  
LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection -Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	84%
Lamp flux	7200 lm	ULOR	3%
Luminous efficacy	68 lm/W	Total flux	6017 lm
CCT	3000 K	Total power	89 W
CRI	90		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

## Electric

System power: 89 W

## Protection

IP: 55