Product data sheet

NANO TILT MATT WHITE 4W LED 2700K RA>90 36D

5046907011 SG ARMATUREN



Small downlight with polished reflector for windows, cabinets and niches to give a nice moodful light. Nano is available at 15 or 36 degrees and Nano Tilt, which can be directed, has a 36 degree spread angle. Delivered without driver. Nanodriver (optional) with max 9W and dimmed with 1-10V / pushdim. Light distribution Direct Beam angle: 36° Light technic LED (not exchangeable) 4W (excluding driver) 2700K or 3000K Ra>90 SDCM: 2 L70/B50 >50,000 hrs Ta=25°C Control/Dimming Driver 350mA ordered separately Protection Class III IP44 Energy and approvals A CE Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Glass Mounting/Connection Recessed (downlight)

Light output 1 (integrated)

|--|

| · I· · / I· · |
|--------------------|
| Nominal lamp power |
| Total flux |
| Luminous efficacy |
| |

Lamp type

44

| LED | |
|--------|--|
| 4 W | |
| 240 lm | |
| 0 lm/W | |

CCT

CRI

LOR

Total power

2700 K 100%

90

4 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 1.89 in Width: 1.89 in Height: 1.17 in

Adjustability

Tiltable

Design

Color of housing: White

Electric

60

System power: 4 W Appliance Class: III

Protection

IP: 44