## Product data sheet

FLEX STRIP SUNLIKE 300 - SWW L6833226

PROLED (MBN GMBH)








The PROLED FLEX STRIPS are perfect for indirect lightning, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities. - Very high color rendering index (CRI 98). Natural light near the spectrum of the sun light. - High flexibility - adaptable to round shapes. - Installation with 3M adhesive tape on the strip's backside (self adhesive). - dimmable and controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies/controller

## Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	10 W	CRI	98
Total flux	700 lm	LOR	100%
Luminous efficacy	70 lm/W	Total power	10 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.37 in Width: 0.31 in Height: 0.08 in

Adjustability

Fixed

Electric

System power: 10 W

Controller: Dimmable 1..10V, DMX, DALI

Appliance Class: III

Protection

IP: 20

Other operating numbers

Ambient temperature range: 14...113°F