




# Product data sheet

MONDANA-E  
551100.002.12  
RZB



Series: Mondana Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic (polycarbonate), microtextured finish. Diffuser fastening: screw fitting. Diffuser: plastic (polyethylene), opal, satin finish. With Gore-TM Protective Vents membrane valve as standard. Recessed housing: metal, powder-coated, for installation in cavity walls with 10-30 mm wall thickness. Available Colours: pure white (RAL 9010) Type of Installation: Recessed ceiling mounting, Wall (recessed) Dimensions: D 650, H 2 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1850lm System power: 21W Beam Angle: 114° Number of fittings B10A: 77 Number of fittings B16A: 124 Number of fittings C10A: 77 Number of fittings C16A: 124 Inrush current: 0,1A Unified Glare Ratio: 19,0 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	1850 lm	LOR	100%
Luminous efficacy	88 lm/W	Total power	21 W

## Mounting mode

Wall recessed

## Shape and measurements

Height: 0.04 in  
Diameter: 25.59 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 21 W

## Protection

IP: 65  
IK: 10