


Product data sheet

EPSYLON - POLE TOP LIGHT
7210-0-3-611-XX
UNILAMP



EPSYLON is the family of pole top and wall mount luminaires with unshielded symmetrical distribution. The recommended mounting height is between 3 – 5 meters. To avoid discolouration of the lens we have used a high quality PMMA clear cover. The diffuser gives a broad spread light distribution. These luminaires are generally used to illuminate gardens, parks, pedestrian, squares and open spaces. They are assembled with high brightness multiple LEDs. Aluminium pole, galvanized steel pole, pole adaptor and anchorage unit for concrete foundation are also available. • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Spun Aaluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Clear PMMA diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • M20 cable gland or TPE grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	60%
Lamp flux	6000 lm	ULOR	10%
Luminous efficacy	86 lm/W	Total flux	3576 lm
CCT	1690 K	Total power	83 W
CRI	36		

Mounting mode

Pole top mounted

Shape and measurements

Length: 24.03 in

Width: 24.40 in

Height: 17.64 in

Adjustability

Fixed

Electric

System power: 83 W

Appliance Class: I

Protection

IP: 54

IK: 06