

# Product data sheet

FLAT POLYMERO  
311556.002.5.76  
RZB




IP  
40

IK  
03

Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 620, H 160 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3100lm System power: 28W Beam Angle: 116° Number of fittings B10A: 22 Number of fittings B16A: 40 Inrush current: 34A Unified Glare Ratio: 18,4 EEC: A++

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 28 W     | CRI         | 80     |
| Total flux         | 3100 lm  | LOR         | 100%   |
| Luminous efficacy  | 111 lm/W | ULOR        | 11%    |
|                    |          | Total power | 28 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 6.30 in  
Diameter: 24.41 in

## Adjustability

Fixed

## Electric

System power: 28 W

## Protection

IP: 40  
IK: 03